

LITHIUM-POLYMER RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

XPR-5554G

# NIGHTSTICK®

Life Depends on Light™

**DUAL  
LIGHT  
TECHNOLOGY**

**IP-67  
DUST/WATER  
PROOF**

**ATEX  
ZONE 0  
IECEx**

**CLASS I  
DIV 1**



**Magnetic Waterproof USB Coupling**  
Never worry about water getting inside your headlamp.



**Dual-Light Technology**, focused spotlight and area floodlight at the same time.



**ANSI IP-67 Dustproof / Waterproof** with a 2 meter drop rating.



Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



**MULTI-POSITION  
TILT-HEAD DESIGN**

Includes NS-HMC9 and Stainless Steel Clip Back Plate for zero band application.



## 160 LUMENS

1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

## DUAL-FUNCTION HEADLAMP

## RECHARGEABLE

## ITEM NUMBER/UPC

- XPR-5554G, UPC 0 17398 80788 3

## MARKET APPLICATIONS

- Hazardous work environments, industrial, fire & rescue

## CERTIFICATIONS

- cULus, CE, ATEX, IECEx, InMetro, UKCA, KOSHA

## CASE MATERIAL

- Engineered Polymer

## SPOTLIGHT LUMENS/RUNTIME

- HIGH: 130L, 7.5 hrs. runtime  
- LOW: 70L, 16 hrs. runtime

## FLOODLIGHT LUMENS/RUNTIME

- HIGH: 130L, 6.5 hrs. runtime  
- LOW: 70L, 12.5 hrs. runtime

## DUAL-LIGHT LUMENS/RUNTIME

- 160L, 4.5 hrs. runtime

## CANDELA

- HIGH: 1,887

## BEAM DISTANCE

- 87m

## DUST/WATER RATING

ANSI IP-67 Dustproof / Waterproof

## DROP RATING

- 2 meters

## DIMENSIONS

- LENGTH: 2.1 in (53 mm)  
- WIDTH: 2.6 in (66 mm)  
- DEPTH: 1.8 in (46 mm)  
- WEIGHT: 3.0 oz (85 g)

## BATTERY







- Lithium-Polymer (integrated)

## WARRANTY



- Limited lifetime warranty

## WHAT'S INCLUDED

- Headlamp  
- Lithium-Polymer battery  
- Elastic non-slip headband  
- Heavy-duty rubber head strap  
- Strap Back Plate  
- Stainless Steel Clip Back Plate  
- NS-HMC9 Mount  
- 4' (304 mm) USB Male (Type A) Magnetic Coupler Charge Cord  
- Alcohol prep pad  
- Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	130 LUMENS	70 LUMENS	160 LUMENS
	7h 30min	16h	4h 30min
	87m		
	1887cd		
	2m		
	1m		


**Segurança**






OCP 0034 INMETRO  
Ex ia IIC T4 Ga  
(20°C ≤ Tamb ≤ +40°C)  
NCC 21.0077

**Bayco Products, Inc. XPR-5554G**  
640 S. Sanden Blvd., Wylie, TX 75098


Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS  
For use with Bayco Li-Ion Battery Pack 5554-BATT

 LISTED  
E 467756  
ID 4003544  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

 0359  2575

SEE INSTRUCTION MANUAL  
VOIR MANUEL  
ATENÇÃO - VER MANUAL DE INSTRUÇÕES

CLASS I DIV 1 GRPS A-D T4  
CLASS II & III DIV 1 GRPS E-G T135°C  
CLASS I ZONE 0 AEx ia IIC T4 Ga  
Ex ia IIC T4 Ga  
Ex ia IIC T4 Ga  
UL 20 ATEX 2400  
UL22UKEX2431  
IECEX UL 20.0080  
-20°C ≤ Tamb ≤ +40°C  
3.7V/Cell 5554-BATT  
Um 4.2V

 22-AMBO-0218X

MFG MM-YY

CERTIFIED

