



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEX UL 20.0036** Page 1 of 3 [Certificate history:](#)

Status: **Current** Issue No: 0

Date of Issue: 2020-05-27

Applicant: **Bayco Products Inc**
640 S Sanden Blvd
Wylie, TX 75098
United States of America

Equipment: **Headlight, Nightstick XPR-5562GX**

Optional accessory:

Type of Protection: **Intrinsic safety "ia", Inherently safe optical radiation "op is"**

Marking: Ex ia op is IIC T4 Ga
-20°C ≤ Tamb ≤ +40°C

Approved for issue on behalf of the IECEx
Certification Body:

Katy A. Holdredge

Position:

Senior Staff Engineer

Signature:
(for printed version)

Date:

2020-05-27

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

UL LLC
333 Pfingsten Road
Northbrook IL 60062-2096
United States of America





IECEX Certificate of Conformity

Certificate No.: **IECEX UL 20.0036**

Page 2 of 3

Date of issue: 2020-05-27

Issue No: 0

Manufacturer: **Bayco Products Inc**
640 S Sanden Blvd
Wylie, TX 75098
United States of America

Additional
manufacturing
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2011 Explosive atmospheres - Part 0: General requirements
Edition:6.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"
Edition:6.0

IEC 60079-28:2015 Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation
Edition:2

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[US/UL/ExTR20.0037/00](#)

Quality Assessment Report:

[GB/ITS/QAR13.0005/07](#)



IECEx Certificate of Conformity

Certificate No.: **IECEX UL 20.0036**

Page 3 of 3

Date of issue: 2020-05-27

Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

Model Nightstick XPR-5562GX is an intrinsically safe LED headlight containing two LEDs, which is powered by one rechargeable Li-ion battery pack Part No. 5562-BATT. The device contains two non-metallic enclosures which contains three printed circuit boards connected by a cable, two black push buttons and a headband.

Please see Annex for additional information.

SPECIFIC CONDITIONS OF USE: NO

Annex:

[Annex to IECEx UL 20.0036 Issue 0.pdf](#)



IECEX Certificate of Conformity

Certificate No.: IECEX UL 20.0036

Issue No.: 0

Page 1 of 1




PARAMETERS RELATING TO THE SAFETY

Um = 4.2 V

Only power the device with one Bayco part number 5562-BATT battery pack.

MARKING

Marking has to be readable and indelible; it has to include the following indications:

 E 467756 ID 4003544 INTRINSICALLY SAFE SECURITE INTRINSEQUE	Bayco Products, Inc. XPR-5562GX 640 S. Sanden Blvd., Wylie, TX 75098 Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS UL listed for use with Bayco Li-ion Battery Pack 5562-BATT CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV 1 GRPS E-G T135°C CLASS I ZONE 0 AEx ia op is IIC T4 Ga ⊕ II 1 G Ex ia op is IIC T4 Ga	Ex ia op is IIC T4 Ga DEMKO 20 ATEX 2267 IECEX UL 20.0036 -20°C ≤ Tamb ≤ +40°C 3.7V/Cell 5562-BATT Um 4.2V
 0359	WARNING: Do not charge battery in a hazardous location WARNING: Do not replace battery when an explosive atmosphere is present	
 SEE INSTRUCTION MANUAL VOIR MANUEL		MFG MM-YY