

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E207119  
**Report Reference** E207119-20160719  
**Issue Date** 2020-APRIL-28

**Issued to:** FEDERAL SIGNAL CORP SIGNAL DIV  
2645 FEDERAL SIGNAL DR  
UNIVERSITY PARK IL 60484-3167

**This certificate confirms that  
representative samples of**

VISUAL-SIGNAL APPLIANCES FOR USE IN  
HAZARDOUS LOCATIONS  
SEE ADDENDUM PAGE

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:**

UL 121201, CAN/CSA C22.2 No. 213-17, Nonincendive  
Electrical Equipment for Use in Class I and II, Division 2  
and Class III, Divisions 1 and 2 Hazardous (Classified)  
Locations.

UL 1638, CAN/ULC-S526, Standard for Safety for Visible  
Signaling Devices for Fire Alarm and Signaling Systems,  
Including Accessories.

**Additional Information:**

See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E207119  
**Report Reference** E207119-20160719  
**Issue Date** 2020-APRIL-28

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL, CNL – Visual signal devices for use in Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Group F and G, and Class III Hazardous Locations.

USL - Signaling appliance for the hearing impaired for use in hazardous locations, Class I, Division 2, Groups A, B, C, and D; Class II, Division 2, Group F and G, and Class III Hazardous Locations.

G Series Strobe, Model G-STR; followed by -024, -120, or -230; may be followed by -E, -D, or -T; may be followed by -C, -G, -M, -Y, -R, -A, -B, or -X may be followed by -15J.

G Series LED, Model G-LED; followed by -DC or -AC; may be followed by -E, -D or -T; may be followed by -C, -G, -M, -Y, -R, -A, -B, or -X; may be followed by -H.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

