



Clock

Ex-Time 40

- With Quartz movement
- Sturdy metallic housing
- Simple and uncomplicated time setting

Explosion-protected quartz wall clock



Technical Data

| | |
|--|--|
| Electrical specifications | |
| Battery type | 1x LR14 according to IEC (type-tested) |
| Operating duration | 1 year |
| Measurement accuracy | |
| Accuracy | -5 / +15 seconds per month |
| Ambient conditions | |
| Ambient temperature | 0 ... 50 °C (32 ... 122 °F) |
| Mechanical specifications | |
| Mass | approx. 2 kg |
| Dimensions | 400 mm x 60 mm |
| Data for application in connection with hazardous areas | |
| EU-type examination certificate | PTB 02 ATEX 2197 X |
| Marking | Ⓜ II 2 G Ex ia IIC T4 Gb |
| International approvals | |
| SGS approval | |
| SGS certificate | SGSNA/22/SUW/00077X |
| SGS marking | Class I, Division 1, Groups A, B, C, D, T4 |
| UKCA approval | |
| UKCA certificate | CML 21UKEX 21404X |
| UKCA marking | Ⓜ II 2G Ex ia IIC T4 Gb |
| General information | |
| Scope of delivery | Ex-Time 40 Batteries Documentation |

Release date: 2022-10-18 Date of issue: 2022-10-18 Filename: 70135099_eng.pdf