



APPLIED RESOLUTION TECHNOLOGIES

Laser application technologies : Mining, Oil & Gas, Agriculture, Industrial

www.appliedresolution.com.au

BLX-635S3C

INTRINSICALLY SAFE, IECEx CERTIFIED LASER FOR ANY HAZARDOUS ENVIRONMENT USE.

35 YEARS OF EXPERTISE IN LASER APPLICATIONS TECHNOLOGY HAS CULMINATED IN THE BLX-635S3C, TWICE THE RANGE OF OTHER Intrinsically Safe (IS) LASERS. SAFE. TOUGH. EFFICIENT. INTEGRATED BATTERY MODULE, NOT REMOVABLE



The BLX-635S3C is a Class 2M alignment laser system used in hazardous environments such as underground mining or conveyor alignment applications. The laser is robust enough for the toughest environment. The BLX-635S3C is a sensor enabled red version of the red BLX-515S5C which will work with laser sensing systems.

It's visible red beam is safe to use under all conditions, and the precision alignment of the laser beam axis to the body axis allows simple and precise alignment. **Range is OVER 700 metres!!!**

Intrinsically safe by design. Tough. Rugged. Efficient. Safe.

FIXED BATTERY MODULE VERSION!!!

HIGHLY VISIBLE. TOUGH. ROBUST. SAFE. ART has been at the forefront of new direct intrinsically safe diode technology since 2009. The BLX-635S3C laser with FIXED battery module is the pinnacle of laser alignment device performance, reliability and versatility.

The BLX-635S3C uses 3 x C-cell batteries. The integral battery version is a different product but with identical performance to the popular removable battery version BLX-635S, but is **NOT** convertible to a removable battery module system.

CERTIFICATION

- **IECEX SIM 13.0005** Ex ia I/IIB T1
- Certified to IEC 60079.11 : 2011
- Supported by Quality Management to IEC 80079-34
- Supported by IECEx SIM S0003 Service Facility Certification
- The BLX-635S3C laser has a 20mm diameter exit beam, which enables up to 5mW laser power for Class 2M under IEC 60825-1. Includes an adjustable IRIS for close-range alignment.

APPLICATIONS :

- Underground survey and alignment
- Continuous Miner guidance
- Tunnelling, boring
- Tunnel and excavation guidance
- Coal Conveyor Alignment
- Mining and Industrial Automation
- Oil and Gas facility alignment...

Manufactured, maintained and serviced in Australia.

Specifications :

- Visible laser 635nm (red)
< 5.0mW in 20mm diameter, Class 2M
- Working range > 700 m
- Compliant with Standards :
IEC 60079-0:2019
IEC 60079-11:2019
IEC 60825.1:2011
- 300 mm long
- Beam aligned to laser body using proprietary means.
- 3 C-Cell battery version
- FIXED (non-removable battery module)
- Reverse battery polarity protection and in-built fusing for intrinsic safety compliance
- Long battery life
- Simple rotary on/off switch with nylon-tipped set screw lock.
- Protective laser window
- Certification information engraved into the laser body for permanent label.
- Included iris accessory
- FRAS approved mounting and adjustment systems

AUTOMATION READY WITH MODULATION