

### EPF-10P.3-100

## Explosion Proof Electric Inline Axial Fan - 100ft Cord - 15' Conductive Duct - 1/3 HP Engine - C1D1

Product ID: 68846

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

#### EPF-10P.3-100 Proof Inline Axial Fan

Air consumption: 38 cfm  
Voltage: 115 VAC  
Amps : 86 DbA12.6  
Motor: 1/3 Horsepower  
CFM Delivery : 1390  
Noise Level: 72 dbA @ 3ft  
Fan Type: Inline Axial Fan  
Size: 16"W x 16.75"H x 12.5"D  
Wiring: 100 Foot Cord w 5-15 Exp Proof Plug  
Protection: Dual Lug Ground Body/Automatic Reset Thermal Overload

#### UL and C-UL Listed

Class I, Div. 1, Groups C and D  
Class II, Div. 1, Groups E, F, G  
T4 Temp rating -30C to 160C  
Meets UL and Canadian UL Safety Ratings

#### Special Orders - Special Requirements

Contact us for special requirements  
Toll Free: 1-800-369-6671  
Intl: 1-903-270-1187  
Fax: 1-903-498-3364  
E-mail: [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

#### **Made in the USA**

The Larson Electronics EPF-10P.3-100 Explosion Proof Electric Inline Axial Fan with 21 foot static conductive duct is UL and CUL listed and safely and effectively redirects stale air from hazardous location areas. This fan includes a 15 foot static conductive duct and a shorter 6 foot conductive duct, is designed for portability, and can be linked in series when larger lengths of conductive duct are needed.

This explosion proof fan delivers high-performance airflow with a 1,390 overall CFM rating and 973 CFM when fitted with a 25ft. duct and a 90 degree bend. The 1/3 horsepower electric motor runs from standard 115 VAC and pulls 12.6 amps. Added safety features include a prewired explosion proof switch, dual grounding lugs on the

steel housing, and 100 feet of cord fitted with a 5-15 straight blade explosion proof plug. Meets UL and Canadian UL safety ratings for Class 1, Division 1, Groups C and D & Class II Division 1, Groups E, F and G.



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)

This explosion proof fan is designed for portability and durability with a light weight compact body constructed of powder coated steel and a non-sparking aluminum blower wheel. Rubber coated base feet and an integral carry handle provide easy transport and secure placement when set down on a flat surface. This unit is available with either an 8 inch or 10 inch intake and exhaust flange, and includes a built in automatic reset thermal overload for added protection.

**Note on Explosion Proof Fans:** Can be used as an intake and an exhaust fan.



[Exhaust Configuration](#)

[Intake Configuration](#)

#### Features:

#### INCLUDES:

1. Hazardous location ventilation fan (blower)
2. 15 feet static conductive duct
3. 6 feet static conductive duct
4. Dust carrier (holds up to 50ft. of duct)
5. Universal mount
6. Static conductive 90 degree elbow for saddle vent
7. Static conductive saddle vent

- 1/3 HP electric motor, 115 VAC, 12.6 amp
- Explosion-proof switch installed and wired
- 8 or 10 inch intake and exhaust flange
- 1390 cfm free air delivery
- 973 cfm when a 25ft. duct and a 90 degree bend are present while in use.
- 72 dbA @ 3ft.
- Approved for Class I, Div. 1, Groups C and D and Class II, Div. 1, Groups E, F, G
- Aluminum non-sparking blower wheel
- Dual grounding lugs installed on steel housing
- All Steel, powder coated red with rubber base feet
- Automatic reset thermal overload
- Carry handle frame
- Pre-Wired With 100 Ft. Cord
- Pre-wired with a 15 amp explosion proof 5-15 style plug

The ducts on this fan consist of single-ply polyester reinforced PVC vinyl fabric hose with an external wear strip reinforced with a spring steel wire helix. The ducting is lightweight for these blower applications and is highly compressible. The retractability of the static conductive duct allows for convenient storage and easy transport in a fraction of its fully extended length and has low friction loss. The wearstrip offers external abrasion resistance, and is listed as YL 94 V-0 flame retardant. Ambient temperature for the fan ranges from -20 degrees to 180 degrees Fahrenheit.

Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.498.3364

---

---

## Frequently Asked Questions (FAQ)













**EPF-10P.3-100**

**Product ID: 68846**

**Export Control Classification Number (ECCN): EAR99**

Links (Click on the below items to view):

- [Operations Manual](#)
- [SpecSheetSpanish](#)
- [Spectrum Curve \(Wavelength Graph\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [Video1](#)
- [Video2](#)
- [Video3](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)