



## DT311YR Rugged Tablet

### Slim, Rugged, Multi-Functional Wireless Computing

The DT311YR Rugged Tablet features the integration of high-brightness 11.6" touchscreen and a high-performance, energy-efficient Intel® Core™ processor within a slim, lightweight, durable package. With built-in smart card/CAC reader and Wi-Fi, as well as optional data capture modules, this robust tablet offers seamless information capture and transmission for improved workflow. Rated IP65, MIL-STD-810H/461G, and HERO certified with a wide temperature range, the DT311YR Rugged Tablet provides reliable operation in harsh, mission-critical environments.

#### Features

- 11.6" full-HD capacitive 1000 nits touchscreen, digital pen support
- Intel® Core™ i5/i7 processor
- Microsoft® Windows® 10/11 IoT Enterprise operating system
- NIST compliant BIOS available
- High capacity, hot-swappable battery pack
- Built-in smart card/CAC reader
- Anti-microbial coating
- IP65 rated, MIL-STD-810H and MIL-STD-461G certified
- HERO (Hazard of Electromagnetic Radiation to Ordnance) certified
- Slim keyboard option for 2-in-1 applications
- Quick access SSD
- Energy Star 8.0 certified



#### Major Options

- Long range BT Class 1 (1000 ft)
- Front and back cameras
- 2D barcode scanner (reads 1D and 2D)
- UHF RFID reader
- GPS module
- 4G LTE/AWS
- C1D2 configurations available

# Specifications



<b>Model</b>	<b>DT311YR</b>
<b>System</b>	
<b>CPU</b>	Intel® Core™ i7-1355U, 10-core, up to 5.0 GHz Intel® Core™ i5-1335U, 10-core, up to 4.6 GHz
<b>RAM</b>	8GB to 32GB
<b>Storage</b>	512GB to 2TB flash *Support quick access SSD function to easily replace the SSD without opening the back cover.
<b>Operating System</b>	Microsoft® Windows® 10/11 IoT Enterprise
<b>NIST Compliance</b>	NIST compliant BIOS available
<b>Display</b>	11.6" LED-backlit, high-brightness 1000 nits touchscreen
<b>Display Resolution</b>	1920 x 1080
<b>WLAN</b>	Wi-Fi 802.11ax, 2.4/5/6 GHz dual band
<b>Microphone</b>	Built-in microphone
<b>Speaker</b>	Built-in speaker
<b>Smart Card/CAC Reader</b>	Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card
<b>Buttons</b>	1 x power button; 2 x brightness buttons; 5 x programmable buttons
<b>I/O Ports</b>	
<b>USB Ports</b>	1 x USB 3.0, 1 x latest USB/charging
<b>Ethernet Port</b>	1 x Ethernet 10/100/1000MB Base-T LAN
<b>Headphone Jack</b>	1 (3.5 mm)
<b>DC-in Jack</b>	1
<b>Mechanical and Environmental</b>	
<b>AC/DC Adapter</b>	Input: 100 to 240V AC; Output: 19V DC, 3.42A
<b>Enclosure</b>	ABS + PC plastic and magnesium-aluminum alloy
<b>Battery Pack</b>	60W Hot-swappable battery (11.4V, 5400mAh) (Optional) 90W Hot-swappable battery (11.4V, 8000mAh)
<b>Dimensions (H x W x D)</b>	8.3 x 12.4 x 0.86 in/212 x 316 x 21.9 mm
<b>Weight</b>	3.5 lbs/1.6 kg
<b>Temperature</b>	Operation*: -10°C to 60°C (14°F to 140°F) Optional -30°C to 60°C (-22°F to 140°F) with a built-in heating element. *For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F) Storage: -50°C to 70°C (-58°F to 158°F)
<b>Humidity</b>	0% to 90% non-condensing
<b>Certifications</b>	CE, FCC Class B, RoHS, Energy star 8.0
<b>Durability</b>	IP65, MIL-STD-810H and MIL-STD-461G certified
<b>Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing</b>	Yes
<b>Major Options</b>	
<b>Barcode Scanner</b>	2D barcode scanner (reads 1D and 2D)
<b>Camera</b>	2 MP front camera and 8 MP back camera
<b>UHF RFID Reader</b>	865 to 928MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; 30 ft (9.14m) reading distance
<b>GNSS</b>	GPS
<b>Mobile Broadband</b>	4G LTE/AWS
<b>Long Range BT</b>	Class 1 BT (1000 ft)
<b>Certification</b>	C1D2

\* Specifications subject to change without notice.

# Accessories

The DT311YR Tablet has customized accessories to meet numerous deployment needs.

<b>Digital Pen</b>	
<b>Pen Tip</b>	Diameter: 0.059 in/ 1.5mm, replaceable
<b>Buttons</b>	2 side buttons (right-click and eraser)
<b>Battery</b>	1 AAAA, replaceable
<b>Color</b>	Black
<b>Dimensions</b>	Length: 5.5 in/ 140 mm (including pen tip) Diameter: 0.38 in/ 9.7 mm
<b>Weight</b>	0.055 lbs/ 25 g



<b>Slim Detachable Keyboard</b>	
Designed to connect to DT311YR tablet without switching and pairing	



<b>Handstrap with Kickstand</b>	
With rotatable, adjustable handstrap and foldable kickstand	



<b>Desktop Charging Cradle</b>	
Docking support with ports for Power, USB, HDMI output and Ethernet	



<b>Wall/ Vehicle Mount Cradle</b>	
Offers tablet storage and security with power supply and I/O ports.	



<b>Battery Charging Kits</b>	
	



<b>Carrying Case</b>	
	

<b>High Capacity Battery Pack</b>	
	

**Product Configurator**

[www.dtresearch.com/productconfig](http://www.dtresearch.com/productconfig)