



GENERAL INFORMATION			
MODEL	R-PT-R-EX	RATING	Built to U/L 583 Type "EX", FM Approved, Class I-D, II-G Div.1
MODEL DESCRIPTION	Heavy Duty "EX" Stand Up Rider Tractor	STANDARDS MET	ANSI/ITSDF B56.9
ROLLING LOAD CAPACITY	15K Rolling Load	RICO DEC CODE	
MAXIMUM DRAWBAR PULL RATING		TRUCK VOLTAGE	24
NOMINAL DRAWBAR PULL RATING		PAINT	Safety Orange Paint
CAPACITY	NA	STEERING	Power
LOAD CENTER	NA	STEERING CONTROLS	Steering Hand-wheel for LH Operation
DRIVE TYPE	Single Vertical Transmission	PRIMARY FUNCTION CONTROLS	
TRAVEL SPEED	3 MPH Empty	SECONDARY FUNCTION CONTROLS	None
GRADE	5%	LENGTH RESTRICTIONS	
OPERATOR STATIONS	Single	WIDTH RESTRICTIONS	
OPERATOR INTERFACE	Stand Up Rider - Forward Facing	HEIGHT RESTRICTIONS	
TRAVEL CONTROLS	Throttle Control Handle for RH Operation	TURNING RADIUS RESTRICTIONS	
SERVICE BRAKES	Heavy-duty Mechanical Disk brake system	RIGHT ANGLE STACK RESTRICTIONS	
EST OVERALL LENGTH	52" Plus Hitch	WEIGHT RESTRICTIONS	
EST OVERALL WIDTH	40"		
EST OVERALL HEIGHT	55.8		
EST GROUND CLEARANCE	2"		

LOAD HANDLING INFORMATION			
CUSTOMER TRAILER WHEEL TYPE		HITCH POSITION	Fixed
CUSTOMER TRAILER STEERING TYPE		HITCH HEIGHT	20.5"
HITCH TYPE	See Other Notes		



### ADDITIONAL INFORMATION

SAFETY FEATURES	BDI;Dead-man Braking;Emergency Power Disconnect;Horn;Key Switch;Hour Meter
CUSTOMER SUPPLIED ITEMS	
OTHER NOTES	Quick Disconnect Hitch One for Each: auto coupler, ring, and pin.

### BATTERY & CHARGER INFORMATION

BATTERY SUPPLIED BY	Rico	BATTERY VOLTAGE	24 VDC
BATTERY SUPPLY CONDITIONS		BATTERY QUANTITY PER TRUCK	1
CHARGER SUPPLIED BY	Rico	BATTERY ROLLERS	No
CHARGER SUPPLY CONDITIONS		BATTERY REMOVAL	Overhead