

ATEX certificated Ex-proof IP Camera



Contact Person: Steven | Email: Steven@kaixuantec.com | Tel: +8615280435154

Photo	Model	Resolution	Lens	EX level	Features
-------	-------	------------	------	----------	----------

EX-proof IR Bullet Camera

Photo	Model	Resolution	Lens	EX level	Features
	KX-EX707PW2	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof, anti-corrosion, waterproof IR distance: 50/100m (optional)
	KX-EX707PW218	2.0 Megapixels	4.7-84.6mm (18X)	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V for optional heater optional
	KX-EX701PWC2	2.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof, anti-corrosion, waterproof IR distance: 10-30m lens: 4/6mm for optional Support ONVIF, support HIKVISION, DAHUA DC12V for optional

1. Optional function: AC220/POE (Extra 20USD)

2. Default price 304 stainless steel. Optional material: 316L





EX-proof Bullet Camera (without IR)

Photo	Model	Resolution	Zoom Ratio	EX level	Features
	KX-EX600PW20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof, anti-corrosion, waterproof Support ONVIF, support HIKVISION, DAHUA
	KX-EX600PW218	2.0 Megapixels	18x lens: 4.7-84.6mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	DC12V/AC220V Optional heater Optional
	KX-EX600PWK20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof, anti-corrosion, waterproof m lens: 2.8-12mm
	KX-EX600PWK220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	built-in heater & fan suitable for -45°C ~ +100°C Peltier effect: Automatic cooling >40°C, <5°C self-heating Support ONVIF, support HIKVISION, DAHUA
	KX-EX600PWY20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof, anti-corrosion, waterproof m
	KX-EX600PWY218	2.0 Megapixels	18x lens: 4.7-84.6mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	built-in smart windshield wiper Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V Optional

1. Default price 304 stainless steel. Optional material: 316, 316L




EX-proof Camera Housing

	KX-EX707PW	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof, anti-corrosion, waterproof IR distance: 50-100m inside size: $\Phi 100 \times 300$ mm window size: $\Phi 65$ mm 2*3/4" interface for wire can assemble box camera, all-in one camera heater optional
--	------------	------------------------------------	--	--	---

	KX-EX600PW	housing only without camera inside	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof inside size:Φ100*300mm window size:Φ65mm Suitable for AC220 power 2*G3/4" interface for wire can assemble box camera, all-in one camera heater optional
	KX-EX600PWK	housing only without camera inside	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel, apply to strong corrosive environment don't sell 316, 316L for this housing. Explosion-proof,anti-corrosion, waterproof inside size:Φ100*290mm window size:Φ65mm DC 12V 2*20*1.5mm interface for wire built-in heater&fan suitable for -45℃~+100℃ Peltier effect: Automatic cooling>40℃ .<5℃ self-heating can assemble box camera, all-in one camera
	KX-EX600PWY	housing only without camera inside	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel,(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof inside size:Φ100*290mm window size:Φ65mm optional for DC/ AC220 power 2*G3/4" interface for wire built-in smart windshield wiper can assemble box camera, all-in one camera
	KX-EX01PWFS	housing only without camera inside	High temperature water/air cooling Housing	double-layer structure, auto running water&air compress cold quartz glass window inside size:Φ100*300mm window size:Φ75mm can assemble box camera, all-in one camera 200 degree high temperature


1. Default price 304 stainless steel. Optional material: 316L

3. all models is default is DC 12V. Optional AC 220V(Extra 20USD)

Photo	Model	Resolution	Lens	EX level	Features
	KX-EX1000ZPPS	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M horizontal 360°(Endless) , Vertical: ±90° , Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPY	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M(Laser IR) horizontal 360° , Vertical: ±90° , Horizontal Rotate speed9°/s, Vertical Rotate speed6°/s Auto-Iris, Auto-Focus, Support SD card 256preset, Support ONVIF, support HIKVISION, DAHUA AC220V/24V optional
	KX-EX1000PPS	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless) , Vertical: ±90° , Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V



1. Default price 304 stainless steel. Optional material: 316L

2. KX-EX1000ZPPY Series can add windshield wiper extra 85USD


Photo	Model	Resolution	Lens	EX level	Features
	KX-EX2000PSS			ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	6" inch, 304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof

1. Default price 304 stainless steel. Optional material: 316L



Thermal&HD camera PTZ

Photo	Model	Resolution	Lens	EX level	Features
	KX-EX600PW-R			ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof inside size:Ø100*300mm window size:Φ65mm Suitable for AC220 power 2*G3/4" interface for wire can assemble thermal camera
	KX-EX1000ZPPS-R			ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless), Vertical: ±90°. Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V

1. Default price 304 stainless steel. Optional material: 316L

	KX-EX1000ZPPST50D220-F	2MP day camera; 320 thermal camera	20x visible lens; 50mm thermal lens	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . 8/25/50/75/100mm for optional 640/320 thermal camera for optional Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless), Vertical: ±90°. Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
---	------------------------	---	--	--	--


EX-proof Ptz Camera

Photo	Model	Resolution	Zoom Ratio	EX level	Features
	KX-EX1000ZPPS220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M horizontal 360°(Endless), Vertical: ±90°. Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPS230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	
	KX-EX1000ZPPS320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M horizontal 360°(Endless), Vertical: ±90°. Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPS330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	

	KX-EX1000ZPPY220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M(Laser IR) horizontal 360°, Vertical: ±90°, Horizontal Rotate speed9°/s, Vertical Rotate speed6°/s Auto-Iris, Auto-Focus, Support SD card 256preset, Support ONVIF, support HIKVISION, DAHUA AC220V/24V optional
	KX-EX1000ZPPY230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	
	KX-EX1000ZPPY320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M(Laser IR) horizontal 360°, Vertical: ±90°, Horizontal Rotate speed9°/s, Vertical Rotate speed6°/s Auto-Iris, Auto-Focus, Support SD card 256preset, Support ONVIF, support HIKVISION, DAHUA AC220V/24V optional
	KX-EX1000ZPPY330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	
	KX-EX1000PPS220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless), Vertical: ±90°, Rotate speed0.1°/s~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000PPS230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	
	KX-EX1000PPS320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless), Vertical: ±90°, Rotate speed0.1°/s~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000PPS330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	

1. Default price 304 stainless steel. Optional material: 316L


EX-proof Speed Dome camera

Photo	Model	Resolution	Zoom Ratio	EX level	Features
	KX-EX2000PSB20	2.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof lens: 4/6/8mm for optional Support ONVIF, support HIKVISION, DAHUA

1. Optional function: POE(50USD 6 inch only)

2. Default price 304 stainless steel. Optional material: 316L

EX-proof Pan/Tilt

Photo	Model	Load Type	Lens	EX level	Features
	KX-EX900PPY	Side load	NO	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°, Vertical: +75°~-90° Burden weight ≅ 20kg AC220V/24V optional

1. Default price 304 stainless steel. Optional material: 316L


EX-proof Control Box

Photo	Model	Material	Size(outer)	EX level	Features	
	KX-EX09CB41	304 stainless Steel	135mm*135mm*90mm	IIB	304 stainless steel Explosion-proof,anti-corrosion, waterproof 4"G3/4" interface Medium anti-corrosion	
	KX-EX09CB42	304 stainless Steel	200mm*135mm*90mm	IIB		
	KX-EX09CB43	304 stainless Steel	200mm*200mm*90mm	IIB		
		KX-EX09CBD81	304 stainless Steel	200mm*300mm*150mm	IIB	304 stainless steel Explosion-proof,anti-corrosion, waterproof 8"G3/4" interface Strong anti-corrosion
		KX-EX09CBD82	304 stainless Steel	300mm*300mm*150mm	IIB	
		KX-EX09CBD83	304 stainless Steel	300mm*400mm*150mm	IIB	
		KX-EX09CBD84	304 stainless Steel	400mm*500mm*150mm	IIB	
	KX-EX10CBD82	304 stainless Steel	300mm*300mm*150mm	IIC	304 stainless steel Explosion-proof,anti-corrosion, waterproof 8"G3/4" interface Strong anti-corrosion	
	KX-EX10CBD83	304 stainless Steel	300mm*400mm*150mm	IIC		
	KX-EX10CBD84	304 stainless Steel	400mm*500mm*150mm	IIC		
	KX-EX09CBJ41-A	Aluminum	135mm*135mm*90mm	IIB	Aluminum Explosion-proof, waterproof 4"G3/4" interface	
	KX-EX09CBJ42-A	Aluminum	200mm*135mm*90mm	IIB		
	KX-EX09CBJ43-A	Aluminum	200mm*200mm*90mm	IIB		
	KX-EX08CBS44-A	Aluminum		IIC	four way junction box for cable connection	
	KX-EX08CBS44	304 stainless Steel		IIC	four way junction box for cable connection	

1. Default price 304 stainless steel. Optional material:, 316L

2. Optional: built in AC220 to AC 24V(Extra 20USD), built in AC220 to DC 12V(Extra 10USD),






EX-proof IR Lamp

Photo	Model	IR Distance	EX level	Features
	KX-EX700IR50	50M	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof 850NM IR optional for DC12V/AC220 power 2"G3/4" interface for wire
	KX-EX700IR100	100M	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80°C Db	

1. Default price 304 stainless steel. Optional material: 316L

2. Optional: AC220V

Installation accessories

Photo	Model	Material	EX level	Features
	KX-EX18L1000	Rubber&Steel	ATEX Ex d II	3/4 interface, caliber20mm, length1000mm
	KX-EX15L1000	Rubber&Steel	ATEX Ex d II	20*1.5mm interface, caliber 15mm, length1000mm
	KX-EX18L1000S	304 Stantainless Steel	ATEX Ex d II suggest use Stainless steel 304 if IIC environment	3/4 interface, caliber20mm, length1000mm
	KX-EX06BS	304 stainless steel	---	Suitable for all IR bullet and explosion proof housing
	KX-EX01BY	304 stainless steel	---	suitable for all PTZ and pan&tilt
	KX-EX06BS-W	304 stainless steel	---	Ex-universal joint

1. Default price 304 stainless steel. Optional material: 316L