KAIXUAN

Professional Manufacturer of CCTV Products

www.kaixuantec.com

ATEX certificated Ex-proof IP Camera

Contact Person:Steven|Email:Steven@kaixuantec.com|Tel:+8615280435154

Photo	Model	Resolution	Lens	EX level	Features
EX-proof IR Bullet Camera					
Photo	**Model**	**Resolution**	**Lens**	**EX level**	**Features**
	KX-EX707PW2	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:50/100m(optional) Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V for optional heater optional
	KX-EX707PW218	2.0 Megapixels	4.7-84.6mm(18X)	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	
	KX-EX701PWC2	2.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:10-30m lens: 4/6mm for optional Support ONVIF, support HIKVISION, DAHUA DC12V for optional
1. Optional function: AC220/POE(Extra 20USD) 2. Default price 304 stainless steel. Optional material: 316L					
EX-proof Bullet Camera(without IR)					
Photo	**Model**	**Resolution**	**Zoom Ratio**	**EX level**	**Features**
	KX-EX600PW20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof Support ONVIF, support HIKVISION, DAHUA DC12V/AC220 Optional heater Optional
	KX-EX600PW218	2.0 Megapixels	18x lens: 4.7-84.6mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	
	KX-EX600PWK20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof m lens: 2.8-12mm built-in heater&fan suitable for -45℃-+100℃ Peltier effect: Automatic cooling>40℃ .<5℃ self-heating Support ONVIF, support HIKVISION, DAHUA
	KX-EX600PWK220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	
	KX-EX600PWY20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof m built-in smart windshield wiper Support ONVIF, support HIKVISION, DAHUA DC12V/AC220 Optional
	KX-EX600PWY218	2.0 Megapixels	18x lens: 4.7-84.6mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	
1. Default price 304 stainless steel. Optional material: 316, 316L					
EX-proof Camera Housing					
	KX-EX707PW	**housing only without camera inside**		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:50-100m inside size:Φ100*300mm window size:Φ65mm 2*G3/4" interface for wire can assemble box camera, all-in one camera heater optional

	KX-EX600PW	**housing only without camera inside**	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof inside size:Φ100*300mm window size:Φ65mm Suitable for AC220 power 2*G3/4" interface for wire can assemble box camera, all-in one camera heater optional
	KX-EX600PWK	**housing only without camera inside**	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel, apply to strong corrosive environment don't sell 316, 316L for this housing. Explosion-proof,anti-corrosion, waterproof inside size:Φ100*290mm window size:Φ65mm DC 12V 2*20*1.5mm interface for wire built-in heater&fan suitable for -45℃-+100℃ Peltier effect: Automatic cooling>40℃ .<5℃ self-heating can assemble box camera, all-in one camera
	KX-EX600PWY	**housing only without camera inside**	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(,316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof inside size:Φ100*290mm window size:Φ65mm optonal for DC/ AC220 power 2*G3/4" interface for wire built-in smart windshield wiper can assemble box camera, all-in one camera
	KX-EX01PWFS	**housing only without camera inside**	**High temperature water/air cooling Housing**	**double-layer structure, auto running water&air compress cold** quartz glass window inside size:Φ100*300mm window size:Φ75mm can assemble box camera, all-in one camera 200 degree high temperature

1. Default price 304 stainless steel. Optional material: 316L

3. all models is default is DC 12V. Optional AC 220V(Extra 20USD)

Photo	Model	Resolution	Lens	EX level	Features
	KX-EX1000ZPPS	**housing only without camera inside**		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M horizontal 360°(Endless)，Vertical：±90°， Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPY	**housing only without camera inside**		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M(Laser IR) horizontal 360°，Vertical：±90°，Horizontal Rotate speed9°/s, Verticall Rotate speed6°/s Auto-Iris, Auto-Focus, Support SD card 256preset, Support ONVIF, support HIKVISION, DAHUA AC220V/24V optional
	KX-EX1000PPS	**housing only without camera inside**		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless)，Vertical：±90°，Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V

1. Default price 304 stainless steel. Optional material: 316L

2. KX-EX1000ZPPY Series can add windshield wiper extra 85USD

Photo	Model	Resolution	Lens	EX level	Features
	KX-EX2000PSS	housing only without camera inside, Include bracket and junction box		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	6" inch, 304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof
1. Default price 304 stainless steel. Optional material: 316L					

Thermal&HD camera PTZ

Photo	Model	Resolution	Lens	EX level	Features
	KX-EX600PW-R	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof inside size:Φ100*300mm window size:Φ65mm Suitable for AC220 power 2*G3/4" interface for wire can assemble thermal camera
	KX-EX1000ZPPS-R	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless)，Vertical：±90°， Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
1. Default price 304 stainless steel. Optional material: 316L					
	KX-EX1000ZPPST50D220-F	2MP day camera; 320 thermal camera	20x visible lens; 50mm thermal lens	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . 8/25/50/75/100mm for optional 640/320 thermal camera for optional Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless)，Vertical：±90°， Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V

EX-proof Ptz Camera

Photo	Model	Resolution	Zoom Ratio	EX level	Features
	KX-EX1000ZPPS220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M horizontal 360°(Endless)，Vertical：±90°， Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPS230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	
	KX-EX1000ZPPS320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M horizontal 360°(Endless)，Vertical：±90°， Horizontal/Vertical Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPS330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	

	KX-EX1000ZPPY220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M(Laser IR) horizontal 360°，Vertical：±90°，Horizontal Rotate speed9°/s, Verticall Rotate speed6°/s Auto-Iris, Auto-Focus, Support SD card 256preset, Support ONVIF, support HIKVISION, DAHUA AC220V/24V optional
	KX-EX1000ZPPY230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	
	KX-EX1000ZPPY320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof IR distance:100M(Laser IR) horizontal 360°，Vertical：±90°，Horizontal Rotate speed9°/s, Verticall Rotate speed6°/s Auto-Iris, Auto-Focus, Support SD card 256preset, Support ONVIF, support HIKVISION, DAHUA AC220V/24V optional
	KX-EX1000ZPPY330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	
	KX-EX1000PPS220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless)，Vertical：±90°，Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000PPS230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	
	KX-EX1000PPS320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°(Endless)，Vertical：±90°，Rotate speed0.1°/S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000PPS330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	
1. Default price 304 stainless steel. Optional material: 316L					

EX-proof Speed Dome camera

Photo	Model	Resolution	Zoom Ratio	EX level	Features
	KX-EX2000PSB20	2.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof lens: 4/6/8mm for optional Support ONVIF, support HIKVISION, DAHUA
1. Optional function: POE(50USD 6 inch only) 2. Default price 304 stainless steel. Optional material: 316L					

EX-proof Pan/Tilt

Photo	Model	Load Type	Lens	EX level	Features
	KX-EX900PPY	Side load	NO	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof horizontal 360°，Vertical：+75°∽-90º Burden weight≦20kg AC220V/24V optional
1. Default price 304 stainless steel. Optional material: 316L					

EX-proof Control Box

Photo	Model	Material	Size(outter)	EX level	Features
	KX-EX09CB41	304 stainless Steel	135mm*135mm*90mm	IIB	304 stainless steel Explosion-proof,anti-corrosion, waterproof 4*G3/4" interface Medium auti-corrosion
	KX-EX09CB42	304 stainless Steel	200mm*135mm*90mm	IIB	
	KX-EX09CB43	304 stainless Steel	200mm*200mm*90mm	IIB	
	KX-EX09CBD81	304 stainless Steel	200mm*300mm*150mm	IIB	304 stainless steel Explosion-proof,anti-corrosion, waterproof 8*G3/4" interface Strong anti-corrosion
	KX-EX09CBD82	304 stainless Steel	300mm*300mm*150mm	IIB	
	KX-EX09CBD83	304 stainless Steel	300mm*400mm*150mm	IIB	
	KX-EX09CBD84	304 stainless Steel	400mm*500mm*150mm	IIB	
	KX-EX10CBD82	304 stainless Steel	300mm*300mm*150mm	IIC	304 stainless steel Explosion-proof,anti-corrosion, waterproof 8*G3/4" interface Strong anti-corrosion
	KX-EX10CBD83	304 stainless Steel	300mm*400mm*150mm	IIC	
	KX-EX10CBD84	304 stainless Steel	400mm*500mm*150mm	IIC	
	KX-EX09CBJ41-A	Aluminum	135mm*135mm*90mm	IIB	Aluminum Explosion-proof, waterproof 4*G3/4" interface
	KX-EX09CBJ42-A	Aluminum	200mm*135mm*90mm	IIB	
	KX-EX09CBJ43-A	Aluminum	200mm*200mm*90mm	IIB	
	KX-EX08CBS44-A	Aluminum		IIC	four way junction box for cable connection
	KX-EX08CBS44	304 stainless Steel		IIC	four way junction box for cable connection

1. Default price 304 stainless steel. Optional material:, 316L

2. Optional: built in AC220 to AC 24V(Extra 20USD), built in AC220 to DC 12V(Extra 10USD),

EX-proof IR Lamp

Photo	Model	IR Distance	EX level	Features
	KX-EX700IR50	50M	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	304 stainless steel(316L for optional), apply to strong corrosive environment . Explosion-proof,anti-corrosion, waterproof 850NM IR optonal for DC12V/AC220 power 2*G3/4" interface for wire
	KX-EX700IR100	100M	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP66 T80℃ Db	

1. Default price 304 stainless steel. Optional material: 316L

2. Optional: AC220V

Installation accessories				
Photo	**Model**	**Material**	**EX level**	**Features**
	KX-EX18L1000	Rubber&Steel	ATEX Ex d II	3/4 interface，caliber20mm，length1000mm
	KX-EX15L1000	Rubber&Steel	ATEX Ex d II	20*1.5mm interface，caliber 15mm，length1000mm
	KX-EX18L1000S	304 Stantainless Steel	ATEX Ex d II suggest use Stainless steel 304 if IIC environment	3/4 interface，caliber20mm，length1000mm
	KX-EX06BS	304 stainless steel	——	Suitable for all IR bullet and explosion proof housing
	KX-EX01BY	304 stainless steel	——	suitable for all PTZ and pan&tilt
	KX-EX06BS-W	304 stainless steel	——	Ex-universal joint
1. Default price 304 stainless steel. Optional material: 316L				