



ZONE 1/21

IS520.1

The IS520.1 is an industrial smartphone with current technology. It combines modern design, updated technology and robustness of an industrial product.

) Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.) i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android s a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners.) © 2018 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1015MD03REV01_EN



i.safe MOBILE

TECHNICAL FEATURES



ATEX approval: EX-zone 1/21 (a) II 2G Ex ib IIC T4 Gb Db IP6X



IECEx approval: EX-zone 1/21 Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X



Approved for North America: Class I, II, III Division 1 Groups ABCDEFG, T4 Intrinsically Safe



Approved for Russia: 1Ex ib IIC T4 Gb X Ex ib IIIC T135°C Db X **IP64**



Android™ 7.1



GSM: 850/900/1800/ 1900MHz WCDMA: 900/1800/2100 or 850/1900/2100MHz LTE-FDD: B1/B3/B7/B20/B28 LTE-TDD: B38/B39/B40/B41 TD: B34/B39



5GHz: IEEE 802.11 b/g/n/r/AC with hotspot



Bluetooth® 4.1 LE

external memory microSD up to 32 GB



Qualcomm Snapdragon 625 (MSM8953) 3 GB RAM 32 GB internal memory 22 GB accessible



size: 155 x 80 x 25 mm, weight: 325 g

2 cameras: 8 MP rear camera and 5 MP front



Dual micro SIM



Near Field Communication



SOS-key



magnetic charging port

FURTHER FEATURES

camera



waterproof: 1 hour up to 2 m, impervious to dust and microparticles



operation range from -20 °C to 60 °C



drop-protection, tested against: extreme temperatures, barometric pressure, humidity and vibrations.



4,5" RugDisplay-Glas multi capacitive touchscreen with a resolution of 854 x 480 pixel



usable with gloves



amplified loudspeaker



3600 mAh battery



GPS, AGPS, Glonass, BeiDou



Location, gyroscope, gravity, ambient light, magnetic- and proximity



Push-To-Talk PTT ready (third party application provided)



Loneworker protection LWP ready (third party application provided)



quick charge

CONTENTS

Smartphone, battery, i.safe PROTECTOR 2.0 USB cable, i.safe PROTECTOR 3.0 USB cable, charger, quick start manual and safety instructions