

ZONE 1/21 CL I / DIV 1

i.safe MOBILE < 0 0

IS530.1

Always a step ahead! The smart and innovative Zone 1/Cl I Div1-smartphone with the most advanced technology:

First Bluetooth[®] 5 industrial smartphone with multifunctional ISM interface, a huge internal memory 64 GB and the highest camera resolution of its class.

) Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.) isafe MOBILE and isafe MOBILE logo are registered trademarks of isafe MOBILE GmbH. Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth* is a registered trademark of Google Inc. The Android robot is reproduced or modified from the respective owners.) © 2019 by isafe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1029MD01REV01_EL_0419

WWW.ISAFE-MOBILE.COM

IS530.1



TECHNICAL	FEATURES
-----------	----------

<mark>⟨Ex</mark> ⟩	ATEX approval applied for: EX-Zone 1/21 I 2G Ex ib IIC T4 Gb II 2D Ex ib IIIC T135°C Db IP6X	IEĈEx	IECEx approval applied for: EX-Zone 1/21 Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X		Ð	Approval in North America applied for: Class I, II, III Division 1 Groups A B C D E F G, T4 Intrinsically Safe
	Android [®] 9.0	>	2,4GHz + 5GHz: IEEE 802.11a/ b/g/n/ac/e/k/r/h with max. 8 connections hotspot	4	4G	GSM 850/900/1800/ 1900 MHz WCDMA: UMTS B1/2/4/5/8 LTE-TDD: B38/B39/B40/B41 LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 TD-SCDMA: B34/B39
	Bluetooth® 5.0		Size: 155 x 80 x 25 mm, weight: 325 g			
	External memory microSD up to 128 GB		2 cameras: 13 MP AF rear camera and 5 MP front camera	\langle		Qualcomm Snapdragon SDM660 Octa-Core Kryo Gold-Quad cores 2.2GHz Kryo Silver-Quad cores
	Dual micro SIM	NFC	Near Field Communication			1.8GHz 4 GB RAM 64 GB internal memory 54 GB accessible
sos	SOS-key for additional app		Universal, lateral ISM interface			
FURT	HER FEATURES					
(IP68)	Waterproof: 1 hour up to 2 m, impervious to dust and microparticles		Operation range from -20 °C to 60 °C	8	IL-STD 10G	Drop-protection, tested against: vibrations, shock and extreme temperatures.
	4,5" Gorilla Glass® 3. generation		Usable with gloves			Amplified loudspeaker
	3600 mAh battery, replaceable, 3,8V; 13,68Wh		GPS, A-GPS, Glonass, A-Glonass, Beidou, Galileo		$\overline{\mathbf{I}}$	Location, gyroscope, gravity, ambient light, magnetic- and proximity
PTT	Push-To-Talk PTT ready (third party application provided)		Loneworker protection LWP ready (third party application provided)			Quick charge with magnetic charging port
CONTENTS Smartphone, battery, i.safe PROTECTOR 2.0 USB cable, i.safe PROTECTOR 3.0						

Smartphone, battery, i.safe PROTECTOR 2.0 USB cable, i.safe PROT USB cable, charger, quick start manual and safety instructions