


**RESPONDER**  
**RIGHT ANGLE**

Models on Back | Rechargeable Responder LED

**LIGHTWEIGHT, RIGHT ANGLE FLASHLIGHT IS BEST IN RECHARGEABLE LITHIUM ION BATTERY RELIABILITY.**



**PIERCES THROUGH SMOKE, DUST AND DARKNESS TO A DISTANCE OF 477 METERS!**



**SPECIFICATIONS**

**POWER SOURCE:** Lithium Ion Rechargeable Battery Pack  
**LIGHT SOURCE:** Advanced LED Technology  
**LIGHT OUTPUT:** 205 Lumens  
**PEAK BEAM INTENSITY:** 55,000 candela  
**BEAM DISTANCE:** 477 Meters  
**RUN TIME:** 4 Hours  
**WEIGHT:** 11 oz. with alkaline battery pack  
**LENGTH:** 7.2 in. **WIDTH:** 3.2 in. **DEPTH:** 1.8 in  
**COLORS:** Safety Orange  
 Models and Accessories on Back

**SAFETY RATINGS**

Intrinsically Safe  
 UL Protection Methods  
 UL 913 CSA C22.2 No 157  
 Class I, II, III, Division 1, Groups C - G  
 Class I, II, III, Division 2, Groups C - G  
 Operating temp code T3  
 NFPA 70 504.2 (2008)  
 NFPA 1901-14.1.11.2 (2009)  
 Certified Mounted in any Position

## MODELS

#510221 Rechargeable Responder R/A LED w/ Lithium-Ion Battery Pack & 120V AC Charger

#510221 UTIL Rechargeable Responder R/A LED w/ Lithium-Ion Battery Pack & 120V AC + 12/24V DC Charger

#510318 (Lithium-Ion Version) w/ Direct Wire

#510242 (Lithium-Ion Version) w/ Euro/Int'l charger

#510231 (Lithium-Ion Version) w/ 12/24V DC

#510304 ('AA' Alkaline Battery Version)



## ACCESSORIES

#510201-N: Lithium-Ion Replacement Battery Pack

#510220: Charger Base Only

#510202: Alkaline Battery Tray

#510180: 12/24V DC Charger Cord

#510181: 120V AC Charger Cord

#510182: Euro/Int'l AC Charger Cord