







**WORKSAFE LED LANTERN
 EARNS THE HIGHEST GLOBAL
 SAFETY CERTIFICATIONS OFFERED
 AT THE MOST AFFORDABLE PRICE**

- Intrinsically Safe
- Waterproof, IP 67 rating
- D' Cell Alkaline Batteries
- Switch Guard protects switch on impact
- Glove friendly handle
- ATEX / IECEx Rating Info: 2206 LED ATEX – Zone 1



**LIGHTWEIGHT, LONG RUNNING
 LANTERN FOR ILLUMINATION
 IN HAZARDOUS ENVIRONMENTS**

FL1 STANDARDS

 90 LUMENS	 150 h
 7,000 cd	 1m
 165m	 1m

SPECIFICATIONS

POWER SOURCE: 4 D-Cell Alkaline Batteries
LIGHT SOURCE: LED
LIGHT OUTPUT: 90 Lumens
PEAK BEAM INTENSITY: 7,000 candela
BEAM DISTANCE: 165 Meters
RUN TIME: 150 Hours (alkaline batteries)

MASTER PACK

WEIGHT: 5.8 lbs with alkaline battery pack
LENGTH: 8.2 in. **WIDTH:** 4.9 in. **Height:** 5.6 in.
COLORS: Black Housing, Safety Orange Lens Rim

SAFETY RATINGS

IECEx protection Methods
 Ex ib IIB T3 Gb
 Ex ib IIIB T180°C Db
 -5°C ≤ +40°C

UL protection Methods
 Intrinsically Safe Division 1 and 2
 Class I, II, III Div 1 Groups A-G
 Class I, II, III Div 2 Groups A-G
 T5

ATEX protection Methods

 II 2GD Ex ib IIB T3 Gb
 Ex ib IIIB T180°C Db -5°C ≤ Ta ≤ +40°C

Zone 1

*Safety ratings approvals based on Duracell MN1300 or Energizer E95 cells only