



## 3315RZ0-RA

### Right Angle Light

The unique Peli™ 3315RZ0-RA (Right Angle) LED light is powered by a special designed lithium rechargeable battery that provides a life expectancy of over 2,000 cycles, 4 times more than the 500 cycles that batteries usually last. Lightweight and with three lighting modes (high/low/flashing), it shines up to 132 lumens of clear brilliant light and delivers a run time up to 34 hours in a small compact design. Additionally, this torch features a full time battery level indicator that is conveniently integrated into the switch. Its ergonomic polymer body is engineered with a sure-grip texture.

The 3315RZ0-RA (Right Angle) light is equipped with a right angle adapter with clip that provides hands free lighting. This adapter allows the torch head to articulate, directing the light exactly where you need it.

- Full Time Battery Level Indication
- Ingress Protected IPX7
- 3 modes High / Strobe / Low
- Lanyard (included)
- Special Lithium rechargeable battery provides 2,000 cycles (a 300% increase)
- Up to 132 Lumens
- Up to 34 hours, 15 minutes run time
- Articulating right angle adapter with clip (included)



#### DIMENSIONS

**Length** 8.27" (21 cm)

#### MATERIALS

**Body** Anti-static Impact Modified PC/PBT  
**O-Ring** EPDM  
**Lens** Anti-static coated Polycarbonate (PC)  
**Shroud** Anti-static Impact Modified PC/PBT  
**Clip** Stainless Steel

#### COLOURS

 High Visibility Yellow

#### LIGHT SPECS

**Lamp Type** LED

#### POWER

**Battery Size** 18650  
**Battery Type** Lithium Iron Phosphate  
**Battery Quantity** 1  
**Batteries Included** yes  
**Rechargeable** yes  
**Charge Time** 10 hrs  
**Battery Level Indicator** RGB LED  
**Volts** 3.2v

#### WEIGHT

**Weight With Batteries** 6.2 oz (176 gr)  
**Weight Without Batteries** 3.7 oz (105 gr)

#### SWITCH

**Switch Type** Push Button  
**Light Modes** High / Low / Flashing

#### CERTIFICATIONS

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

ATEX Zone 0






IECEX ia

Document created on 07-27-19

OTHER

**Minimum Pack**  
**Package Code**

1  
C

FL1 STANDARD	HIGH	LOW
	132 LUMENS	15 LUMENS
	5h 0mins	34h 0mins
	108m	35m
	2931cd	308cd
	IP67	

ACCESSORIES