



DU-5K-NI (DU-5K-FSR-NI)

DU-5K-NI Nonincendive Keyboard with FSR

iKey® manufactures devices to reduce risk of failure in your hazardous areas. The nonincendive DU-5K-NI is designed to meet NEMA 4X specifications. It features 116-key functionality, including 24 function keys, and an ABS polycarbonate case. It has a Factory Mutual approval of Class I, Division II. These units include isolation barriers. They and are ideal for harsh working conditions. An upgraded FSR pointing device is integrated into the DU-5K-NI, which offers improved sensitivity and increased durability. (New product code, DU-5K-FSR-NI)
DU-5K-NI (DU-5K-FSR-NI) is an Intrinsically Safe Peripheral IS/NI

Please note: this product is in stock.

Features:

10-Key Numeric Pad

116-Key Functionality

24 Function Keys

Integrated Force Sensing Resistor (FSR) Pointing Device

Polycarbonate Case with Mounting Holes

PS/2 or USB configurations available. PS/2 ships with bulkhead cables. USB ships with PG7 cable gland.

Product Code DU-5K-NI (DU-5K-FSR-NI)

| | |
|-------------------|---|
| CERTIFICATIONS | NEMA 4X, UL60950, FCC Part 15 Class B Factory Mutual Class I, Division II, Gas Groups C, D, E, F, & G. |
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | LENGTH: 5 feet from keyboard to Bulkhead Connector DESIGN: 2 separate cables on PS/2 or single-cable USB |
| KEY SWITCH | MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 6.35 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours |
| POWER | KEYBOARD: 5V@ 10 ma (from CPU port) HULAPOINT: 5V@ 10 ma (from mouse conn. port) |
| COMPATIBILITY | PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F) |

| | |
|---------------|--|
| WEIGHT | 2.6 lbs +/- 0.10 lbs (1.7 kg +/- 0.05 kg) |
| WARRANTY | 1 year limited warranty |
| HUMIDITY | 100% |
| DIMENSIONS | 14.94" x 6.63" x 1.81" (w-h-d) 379.5mm x 168.4mm x 46mm |
| MODEL NUMBERS | DU-5K-NI-PS2: With PS/2 cable DU-5K-NI-USB: With USB cable |