



Instructions

5560-BATT

WARNINGS

- **WARNING:** It is recommended that a qualified technician perform the replacement of the rechargeable battery in this light.
- **WARNING:** Failure to follow these instructions may impair the intrinsic safety of this flashlight.
- **WARNING:** To prevent ignition of a hazardous atmosphere, do not open the battery door in the hazardous environment. This task must only be performed in an area known to be non-hazardous.
- **WARNING:** When exchanging the rechargeable battery, use only the approved 5560-BATT rechargeable battery from Bayco Products.
- **WARNING:** To prevent ignition of a hazardous atmosphere, the rechargeable battery must only be exchanged in an area known to be non-hazardous.

REPLACING THE LITHIUM-ION RECHARGEABLE BATTERY

- Loosen each of the 4 battery door screws the bottom of the light until the battery door comes loose. **CAUTION:** Do not loose these screws. **CAUTION:** Do not allow the battery door gasket to become lost or damaged.
- Remove the old 5560-BATT rechargeable battery. Please recycle the used battery.
- Using only the approved replacement 5560-BATT rechargeable battery from Bayco Products, slide the new battery into the handle of the light using the directional arrow marked on the side of the battery to be a guide to proper battery orientation.
- With the watertight gasket carefully and properly aligned over each of the screw holes, place the base plate back onto the light and hold it in place.
- Fully tighten all 4 of the battery door screws until they are tight. When finished, there should be no gap between the battery door and the handle of the light.

WARRANTY

2-Year Limited Warranty. Go to www.nightstick.com for warranty information.

Bayco Products, Inc. • 640 South Sanden Blvd. • Wylie, TX 75098
1-800-233-2155 • 1-469-326-9400 • www.nightstick.com

INS-5560-BATT-18