

XPP-5422GM

Intrinsically Safe Permissible Dual-Light™ Flashlight w/ Dual Magnets

MARKET APPLICATIONS DESCRIPTION

Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

This Dual-Light™ Flashlight is cETLus, ATEX, IECEx, INMETRO and MSHA listed Intrinsically Safe Permissible. It uses as CREE® LED rated at 120 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 170 meters. A 120 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination. Additionally both the flashlight and the floodlight can be turned on at the same time for maximum versatility. The dual body switches provide momentary or constant-on functionality for the flashlight and on/off functionality for the floodlight. Additionally, the integrated magnets located in the base of the handle and the pocket clip, provide for almost limitless hands-free usage. Power comes from 3 AA premium batteries (not included).

CASE MATERIAL Engineered Polymer - Green

DIMENSIONS Length: 7.2 inches (183 mm) • Head Diameter: 1.8 inches (46 mm) • Handle Diameter: 1.1 x 1.5 inches (28 x 38 mm)

Weight: 6.9 oz. (196 g) with batteries installed WEIGHT

LENS Unbreakable polycarbonate with scratch resistant coating

Flashlight: CREE® LED Impervious to shock with a 50,000 hour lifetime **LIGHT SOURCE LIGHT OUTPUT** Flashlight: 120 lumens, Floodlight: 120 lumens, Dual-Light: 240 lumens

ON/OFF Dual Body Switch - Momentary or Constant-on Flashlight, Constant-on Floodlight

Flashlight: 17.5 hours, Floodlight: 17.5 hours, Dual-Light: 4.5 hours **RUN-TIME**

BATTERY 3 Alkaline AA batteries (not included)

FEATURES

- · cETLus, ATEX, IECEx, INMETRO and MSHA listed Intrinsically Safe Permissible
- Flashlight Floodlight Dual-Light™
- CREE® LED technology 50,000 + hours LED life
- · Momentary or constant-on flashlight
- Sharp focused flashlight beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-light (flashlight & floodlight at same time) for maximum versatility
- Powerful integrated magnets built into the base and pocket clip for multiple hands-free options
- Engineered polymer housing w/ Non-slip grip
- Dual body switches
- Dustproof / Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Includes removable lanyard
- Requires 3 AA batteries

WARRANTY

Permissible Nightstick 5422 Flashlight/Floodlight MSHA

APPROVAL No. 20-A130001-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY WARNINGS: MSHA approved for use with three AA Duracell Type PC1500, Energize Type EN91, and Energizer Type L91 batteries only. Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types. Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only. The Model Nightstick 5422 must not be opened in areas where permissibility is required.



ID 4003544 INTRINSICALLY SAFE SECURITE INTRINSFOUR

CLASS I ZONE 0 AEx ia IIC T3 Ga

CLASS I ZONE 0 Ex ia IIC T3 Ga

⊕ I M 1 Ex ia I Ma



C € 0359

CLASS II & III DIV 1 GRPS E-G T135C Ex ia IIC T3 Ga Intertek ITS 13 ATEX27837X IECEx ETI 13 0026X 1.5V/Cell AA Alkaline

Conforms to:

ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11 ANSI/ISA 60079-26

Certified to:

CAN/CSA STD C22.2 No 157 CAN/CSA STD C22.2 No 60079-0 CAN/CSA STD C22 2 No 60079-11 CSA STD C22.2 No 25

Limited Lifetime Warranty

APPROVALS





