



intelligent light

ADALIT



L-3000

PROFESSIONAL safety torch



ZONE 0

Technology
LedEngine

Functional Features

● TORCH

ATEX Certificate LOM 12ATEX2087 X

II 1G Ex ia IIC T4 Ga | II 1D Ex ia IIIC T85 oC Da

Ingress Protection: IP67

Weight: 500 g

Measures: 225 x 70 mm (L x Diam. Ø)

Burning Time System: 3 different intensity levels that can be chosen by the user in order to choose the correct burning time in every moment with a minimum of 4 hours use of maximum intensity, 6 in the intermediate and 8 hours at the minimum.

Burning time Real time in hours and minutes thanks to the digital display.

Low Battery Warning. Blinking signal of the main LED 15 min. before the batteries get off.

Material: High resistance thermoplastic resin to the impacts, extreme temperatures and corrosive substances. Two button switches of soft touch material, ergonomic and oversized in order to guarantee easy pushing.

Swivelling Head 3 positions: 0° / 45° / 90°

Lighting Source: 2 high intensity LED's with 135 lm.
Total light intensity 200 lm.

Special Double Optic: FLOOD light on - the unique "step lighting system" to light the ground area just ahead user's feet. FOCUSED light on - "BOOSTER" function to illuminate long distances with a greater penetrating light.

Battery: Type Lithium | Voltage: 3,7 V.

Accessories: Holster, Nylon with high visibility.

● CHARGERS

Marking: CE e9

Ingress Protection: IP54

Disconnection at the end of the charge: Automatic

Charge indication: Red LED charging | Green LED charged

Feeding source: DC 12 V. | AC: 100/240 V. 50/60 Hz

Type: Charging rack for 1 torch
Charging rack for 2 torches
Charging rack for 3 torches
Charging rack for 5 torches



L3000

HIGH INTENSITY

200 lumens



10.000 CP

IP67

2m

Lithium



www.adalit.com

●●● The Light Company
ADARO

ADARO Tecnología, S.A.
Parque Científico y Tecnológico de Gijón
-EDIFICIO ADARO-
33203 GIJÓN-ASTURIAS

Customer Service:
Tel.: +34 985 347 806
Fax: +34 985 358 378
info@adalit.com

Catálogo L3000 Mayo/17 Rev0